

What is claimed is:

Sub  
a10

- 5
1. A wireless packetization method in a multimedia transmitting and/or receiving system in a wireless network, comprising the steps of:  
forming a predetermined layer protocol by adding a header to multimedia data which is transmitted through a radio path; and  
adding an error protection code for protecting an error in the header information and a corruption indication flag for indicating corruption of the data, to the header of the predetermined layer protocol.
  2. The wireless packetization method according to claim 1, wherein the corruption indication flag is set as a result of an error when the error protection code for the header information is checked.
  3. A wireless packetization method for a wireless link layer protocol in a multimedia transmitting apparatus in a wireless network, comprising the steps of:  
forming a wireless link layer protocol by adding a header to multimedia data which is transmitted through an application layer; and  
adding an error protection code for protecting an error in the header information and a corruption indication flag for indicating corruption of the data, to the header of the wireless link layer protocol.
  4. The wireless packetization method according to claim 3, wherein the error protection code error-protects between at least one radio link

09783333-024504

protocol (RLP) type information and sequence number information, which are set to the header of the wireless link layer protocol.

5. The wireless packetization method according to claim 3,

6. The method for transmitting a wireless packet according to

7. A method for receiving a wireless packet in a method for

transmitting a RLP frame, in a case where there is no error when a data

setting the corruption indication flag and re-sequencing data of the data

Sub  
ale

the corruption indication flag and discarding the entire frame in a case where there is some error in the header information.

8. The method for receiving a wireless packet according to claim 7, wherein the error protection code on the MUX layer is a code for checking the error of the data field in multiplex-protocol data unit (MUX-PDU).

9. A wireless packetization apparatus for a wireless link layer protocol in a multimedia transmitting system in a wireless network, comprising:

- 5 a header information-creating unit for creating header information  
having an error protection code for protecting an error in a header information relating to multimedia data transmitted through an application layer and a corruption indication flag for indicating corruption of the data; and  
a radio link protocol (RLP) frame-forming unit for forming a radio link  
10 frame by multiplexing the header information formed in the header information-creating unit and the data.

10. An apparatus for receiving a wireless packet in an apparatus for decoding data by receiving a packet in which an error protection code for protecting an error in a header information and a corruption indication flag for indicating corruption of data are added to a header of a radio link layer  
5 protocol, comprising:

